

Shielded Security & Control Cable 22AWG 6/C - CMR

RoHS Compliant

Cables are manufactured to meet current NEC guidelines and are verified by outside standards organizations including (UL)us.



Standard Compliance:

UL 444

Applications

Designed for use in security and alarm systems connecting keypads, sounders/strobes, intercoms, control panels, audio and more.

Specifications

MODELO	LP622W/1000
Construcción:	
Conductor	22AWG 7 Stranded Bare Copper
No. of Conductors	6
Insulation Type	PVC
Color	Black, Red, White, Green, Brown, Blue
Nominal Thickness	0.30 mm
Diameter	1.25 mm
Lay length	65.00 mm
Shielding	Aluminum Foil / Mylar 24AWG Solid Tinned - Copper Drain Wire
Rip Cord	Yes
Color	White (Other colors are available)
Nominal Thickness	0.40 mm
Nominal Diameter	4.20 mm
Electrical & Properties:	
Temperature Rating	-20 to 75°C
Operating Voltage	300 Volts max.
Capacitance	18.5 pf/ft nom.
Impedance	16.9 Ohms nom.
DC Resistance	2.57 Ohms/1000ft @20°C
Flame Rating	UL 1666 (Riser), CMR
Packing:	
Standard Packaging	1000ft Easy Pull Box